



SPECIFICATION
 1.Rating : DC 30V 1.0A
 2.Contact resistance : $\leq 0.03\Omega$
 3. Insulation resistance : $\geq 100M\Omega$ (DC250V)
 4. Withstand voltage : 500VAC
 5. Insertion and extraction Force : 3-20N
 6. Life test : 5,000 cycles

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
5	4#CONTACT FOOT	1	BRONZE	Ag-Plating
4	3#CONTACT FOOT	1	BRONZE	Ag-Plating
3	2#CONTACT FOOT	1	SUS301	Ag-Plating
2	1#CONTACT FOOT	1	SUS301	Ag-Plating
1	HOUSING	1	PAVT	

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
X	±0.30
.XX	±0.20
.XXX	±0.10
.X°	±3.0°
.XX°	±2.0°
.XXX°	±1.0°

UNIT: MM	TYPE:	MODEL NO:	PAPER NO: A4	PAGE 1 OF 1
	PHONE JACK	PJ3013B		SCALE 4:1
DESIGNER BY:				VER 1
CHECK BY:				
APPROVED BY:				

丞永實業有限公司
 BLUE SOURCES ELECTRONICS CO.,LTD.